



JANTEX BLOCKOUT K

- DESCRIPTION:** Jantex Blockout K is a “ready-to-use” blockout developed for use in pigment screen printing. Jantex Blockout K provides exceptional hiding power and bright pigment prints on dyed substrates. The product is compatible with anionic and nonionic binders.
- APPLICATION:** Depending on coverage required, Jantex Blockout K can be extended with cut clear and binder. Add approximately 5 to 10% pigment depending on the desired color.
- PROPERTIES:**
- | | |
|-------------------|-------------------------------|
| Appearance: | Viscous, off-white dispersion |
| Viscosity (25°C): | 7,500-12,000 cps |
| pH: | 8.5 to 10.0 |
| Pounds/Gallon: | 10.3 |
- CURING:** The recommended cure temperature is 330° to 360° F. Cure for approximately 3 minutes.
- CLEAN – UP:** Clean up with water or Jantex Screen Cleaner JT.
- STORAGE:** Keep from freezing and away from direct sunlight. Store between 55 degrees and 95 degrees F. Keep lid closed when not in use. Keep out of the reach of children.
- SAFETY:** Always wear protective eyewear and clothing when mixing color. Refer to M.S.D.S. for additional information.

All recommendations and statements made are based to the best of our knowledge and should under no circumstances be held to without prior testing. Jantex Inks & Beyond, Inc has no control over the conditions of use or storage of the product sold and therefore cannot guarantee the results obtained through use of its product. All products sold and samples given are without representation, warranty, expressed or implied, of fitness for any particular purpose or otherwise, and upon conditions that buyer shall determine suitability of the product for its own purpose. This applies also where protective rights of third parties are involved. It does not release the user from the obligation to test for suitability of the product intended purpose and application.